

Multipurpose

Low

Low shoes



The +

- * Value for money
- * Full grain leather upper
- * Reflective stripe with multiple faces
- * PU2D injected outsole
- * Defined and raised heel

PURCHASE PACKAGING

Référence	Taille	Carton
9AGL010034	34	10
9AGL010035	35	10
9AGL010036	36	10
9AGL010037	37	10
9AGL010038	38	10
9AGL010039	39	10
9AGL010040	40	10
9AGL010041	41	10
9AGL010042	42	10
9AGL010043	43	10
9AGL010044	44	10
9AGL010045	45	10
9AGL010046	46	10
9AGL010047	47	10
9AGL010048	48	10
9AGL010049	49	10

DESCRIPTION

AGATE II is an low safety shoe. Its full grain upper brings a better resistance and breathability than split leather whereas the ankle padding provides supports to the wearer. The polyester mesh lining improves breathability and hence comfort. The out & mid-soles are made of injected polyurethane of different density which balance comfort and durability. This shoe features a steel toe-cap and plate for protection against puncture and fall of heavy objects. The retro-reflective band with patterns improves safety of wearers while in dark environments. AGATE II is equipped with a cleated outsole with good adhesion properties. Ideal for indoor as well as outdoor works.

SECTORS

Infrastructure, building industry

Construction - finishing work

Transport (excluding manufacturing) and logistics

Services and distribution

APPLICATIONS

Luggage handler,
Delivery driver, ...

TECHNICAL FEATURES

Color	Black	Lining	Moisture wicking non-woven membrane
Upper	Full grain leather	Defined heel	
Toecap	Steel		
Puncture resistant sole	Stainless steel		
Midsole	PU		
Outsole	PU		
Insole	Removable, textile and foam		
Main assembly	Injected		
Closing	Lacing closure		

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes, the operation frequency should be stated according to the workstation and carry out a periodic upper treatment with an adequate gloss containing grease, wax, silicone, etc

STANDARD(S)



EN ISO 20345:2011

S3

SRC

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe $0,1M\Omega < A < 1000 M\Omega$ + Fuel and oil resistant contact outsole + Energy absorbing heel $E \geq 20$ Joules + Puncture resistant midsole / Resistant to a 1 100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

RETAILER STAMP